

CARSENSE 303

MAGNETORESISTIVE VEHICLE DETECTOR

Applications

The CarSense 303 features advanced 3-axis, magnetoresistive sensing technology. The sensor measures Earth's magnetic field and responds to disturbances caused by ferrous objects. Three sensing elements provide magnetic field measurement in the X, Y and Z axes, improving detection sensitivity. The CS303's exciting new technology provides a high-sensitivity, compact, and cost-effective solution for reliable vehicle detection.

The small size of the CS303 allows for easy installation in pavement (below grade) with a single saw cut. It provides cost savings on labor and materials when compared to the multiple cuts and corner reliefs required for the installation of inductive loops. The rugged sensor is also suitable for above grade installations, making it ideal for use in confined areas or hidden in non-ferrous architectural components for security purposes.

- Three-dimensional presence detection - select X, Y and/or Z axis independently
- Remote control module for programming and relay contact output
- Stand-alone sensor stores background and settings in a non-volatile memory
- Single cut, low-cost installation
- ULTRAMETER™ sensitivity display for easy set-up
- Fast response for high-speed detection
- Logic Interface available for extended range, directional logic and more
- DETECT-ON-STOP™ feature will allow detection only when a vehicle has come to a complete stop near the sensor. This EMX exclusive technology ignores cross traffic in tight spaces.

CS303



EMX

INDUSTRIES

EMX Industries, Inc.

4564 Johnston Parkway, Cleveland, Ohio 44128

P. 800 426 9912 F. 216 518 9884

Sales Inquiries: salesupport@emxinc.com **Technical Support:** technical@emxinc.com

www.emxinc.com

Applications

- Boom gate control
- Drive-thru and car wash vehicle detection
- Truck/lorry detection at loading docks
- Vehicle counting in car park and toll booths
- Truck and tow-motor detection for industrial gates and doors

Sensitive area vs. Sensitivity adjustment

Area (ft.)	Height at the center (ft.)	Sensitivity (adjustment setting)
1x1	1	2
2x2	2	3
3x3	3	4
4x4	4	6
5x5	5	7



CS303-C-1



CS303-DB-XX



CS303-FP-XX



CS303-L

Technical Data

Sensing technology

ULTRAMETER™ display

Axis sensitivity

Environmental tracking

Local magnetic field nulling

Detection range

Power/fault indicator

Detect indicator

Pulse/presence

Detect-On-Stop™

Outputs

Output ratings

Connection

Operating environment

Housing

Environmental rating

Power supply

Current draw

Supply protection circuitry

Dimensions

Weight

Control Unit

Control Unit & Sensor

Sensor

	3-axis magnetoresistive	
	10 levels of sensitivity: 0-9	
	512 counts/gauss (typical)	
	Automatic compensation	
	Averages local field signature in any sensor orientation	
	5 ft. (1.5m)	
	Green LED	
	Red LED	
	Allows the relay/NPN output to send either a pulse output or have constant presence	
	Requires vehicle to stop for a minimum of 1 second (1-2s typical)	
	SPDT relay/NPN (open collector)	NPN (open collector)
	Relay: 1A @ 24VDC...120VAC NPN: 50 mA (max)	50 mA
	10 position screw terminal	5 conductor direct burial
	-40° C...82° C (-40° F...180° F) 0...95% relative humidity	
	ABS	DB: PVC FP: Polyamide
	IP30	IP69K
	12-30 VDC and 24 VAC	12-30 VDC
	40 mA max	10 mA max
		Reverse polarity and fuse protected
	76mm (3.0") x 22mm(0.9") x 70mm(2.75")	DB:102mm (4.0") x 27mm (1.0") FP: 108mm (4.3") x 22mm (0.9") x 9mm (0.3")
	68g (0.15 lbs.)	DB: 43g (0.09 lbs.) FP: 27g (0.06 lbs.)

Ordering Information

- CS303-C-1 Control Unit
- CS303-DB-50 Direct Burial Sensor, Probe, 50'
- CS303-DB-100 Direct Burial Sensor, Probe, 100'
- CS303-FP-50 Direct Burial Sensor, Flat Pack, 50'
- CS303-FP-100 Direct Burial Sensor, Flat Pack, 100'
- CS303-L Logic Interface, includes black 11 pin socket base DIN rail mount

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 1.9 01/23/19

