

## **MICROWAVE MOTION SENSOR COMPARISON**

GOOD BETTER BEST







## HAWK 2

Microwave

10-20 ft

1

IP66

Manual

## **RAVEN**

Microwave

24.150 GHz

Motion

Bidirectional

## **OWL**

Technology
Operating Frequency
<b>Detection Mode</b>
<b>Detection Direction</b>

**Cross Traffic Rejection** 

**Detection Range** 

**Mounting Height** 

**Environmental Rating** 

**Adjustment Settings** 

Relay

**Differentiate People / Vehicles** 

24.150 GHz

Motion

Bidirectional

Unidirectional approach or depart

NO

vectional approach or depart

NO

YES

NO

YES

3-33 ft (adjustable)

Unidirectional approach or depart

YES

YES

23 ft x 23 ft @ 16 ft (adjustable)

YES
YES
23 ft x 23 ft @ 16 ft (adjustable)

8-23 ft
2 (vehicle & pedestrian)
IP67
Manual or Remote

Microwave & Active Infrared

24.150 GHz

Motion & Presence

Bidirectional

Unidirectional approach

YES

YES

23 ft x 19.7 ft (motion)

18 ft x 26.2 ft (presence)

11.5-21.3 ft

11.5-21.3 ft
2 (motion & presence)

IP65

Remote

EMX Industries, Inc. salessupport@emxinc.com 216.518.9888